
One Leg Eye and Eye Wire Rope Slings



		TYPE 10 (6X26) Tough-Lock™ Mechanical Sling *RATED CAPACITY (TONS)			TYPE 33 (7X7X19) Cable-Flex™ Mechanical Sling *RATED CAPACITY (TONS)			TYPE 30 (6X26) Riggers Hand Splice *RATED CAPACITY (TONS)		
ROPE DIAMETER IN INCHES	EYE SIZE IN INCHES (AXB)	RATED CAPAC- ITY IN POUNDS VERTICAL	RATED CAPAC- ITY IN POUNDS CHOKER	RATED CAPAC- ITY IN POUNDS BASKET	RATED CAPAC- ITY IN POUNDS VERTICAL	RATED CAPAC- ITY IN POUNDS CHOKER	RATED CAPAC- ITY IN POUNDS BASKET	RATED CAPAC- ITY IN POUNDS VERTICAL	RATED CAPAC- ITY IN POUNDS CHOKER	RATED CAPAC- ITY IN POUNDS BASKET
1/4"	2x4	0.65	0.48	1.3	0.5	0.34	1	0.49	0.38	0.99
3/8"	4x8	1.4	1.1	2.9	1.1	0.74	2.2	1.1	0.85	2.1
1/2"	4x8	2.5	1.9	5.1	1.9	1.3	3.7	1.8	1.5	3.7
5/8"	5x10	3.9	2.9	7.8	2.8	1.9	5.5	2.8	2.3	5.6
3/4"	6x12	5.6	4.1	11	4.1	2.8	8.1	3.9	3.3	7.8
7/8"	7x14	7.6	5.6	15	5.4	3.7	11	5.2	4.5	10
1"	8x16	9.8	7.2	20	6.9	4.7	14	6.7	5.9	13
1 1/8"	9x18	12	9.1	24	8.3	5.8	17			
1 1/4"	10x20	15	11	30	9.9	7	20			
1 3/8"	11x22	18	13	36						
1 1/2"	12x24	21	16	42						

